


<u>T4</u>

Now with improved detection of pentane and long chain hydrocarbons

# Portable Multigas Detector









# Portable Multigas Detector

When lives and property are at risk and you need gas detection equipment that is totally reliable, you need Crowcon. For over 45 years Crowcon has been developing and manufacturing high quality products with a reputation for reliability and technical innovation.

Crowcon provide both single gas and multigas monitors for personal monitoring and portable safety applications, providing protection against a wide range of industrial gas hazards. Models vary, but it is Crowcon's philosophy that each should be properly suited to its task.



# Choosing the portable gas detector for your needs

T4 integrates innovative safety features and an intuitive, rugged design to provide advanced protection for those working in harsh environments. This portable multigas detector, which is exceptionally easy to use and service, protects against the four most prevalent gas hazards: carbon monoxide (CO), hydrogen sulphide (H,S), flammable gases and oxygen (O<sub>2</sub>) depletion.



# Confidence, however you look at it

# T4 contains a wide range of features to make everyday use easier and safer:

#### **TWA Resume function**

Unique to T4, this innovative feature ensures toxic gas exposure is calculated accurately over an entire shift, even if T4 is switched off for a break or during travel to another site.

### 18 hour battery life

Safely work multiple or longer shifts between charges, covered by the 18 hour battery life.

#### **Backlit display**

Large, clear display with backlight and option to flip the screen 180° for easy viewing whilst worn.



#### Rugged design

With a thick anti-shock rubber casing and drop tested to 4 metres on concrete, T4 provides dependable operation under the most demanding use. Water & dust resistant to IP65 & IP67.

## **Positive Safety indicator**

A simple 'traffic light' status indicator which, at a glance, provides visual assurance of operational and compliance status to both users and supervisors.

Green light - Working safely



## Intrinsically safe

ATEX approved and UL Class 1 Div 1 for operation in a wide range of hazardous environments.



#### **Dedicated sensors**


One sensor for every gas ensures effective, fast and reliable detection.

# Multiple alarms

Audible 95dB alarm, bright red/blue LED's and vibrating alerts provide effective warning to gas hazards.

### **Easy operation**

Large single button and intuitive menu system minimise training and allow easy operation whilst wearing gloves.



# **TWA Resume**

TWA Resume\* ensures time weighted average (TWA) toxic gas exposure is calculated accurately over an entire work shift.

The red line on the graph shows workers with other detectors risking overexposure to hydrogen sulphide (H<sub>2</sub>S) by switching their detector off for a lunch break.

Only T4 provides the option to include previous measurements in the calculation when you switch your detector back on again and so prevent you exceeding your exposure limit. Because of TWA Resume (green line), T4 alarms at 14:00 when their 8 hour TWA reaches 5ppm.

\* Patent pending - UK patent application number 1501699.1

#### **Product Specification**

Size		135 x 80 x 35mm (5.3 x 3.1 x 1.4in)			
Weight		282g (9.9oz)			
Durability		Drop tested 4m onto concrete			
Alarms	Audible Vibrating Visible	95dB Integrated Bright red & blue LED's			
Display		Front mounted, backlit, 180° flip for easy viewing while worn			
Logging	Data Events	130 hours of data at 10s intervals 3,500			
Battery	Rechargeable Li-ion	Up to 18 hour runtime; 5.5 hour recharge			
Environment	Operating temp Humidity Ingress protection	-20 to +55°C (-4°F to +131°F)* 10-95% RH @ 40°C non-condensing Independently tested to IP65 and IP67			
Compliance	ЕМС	Directive 2014/30/EU			
Approvals	ATEX IECEX UL INMETRO MED	Ex II 2 G Ex d ia IIC T4 Gb Tamb -20°C to +55°C Ex d ia IIC T4 Gb Tamb -20°C to +55°C Use in hazardous locations Class 1 Div 1 groups A,B,C,D only as intrinsic safety Ex d ia IIC T4 Gb Tamb -20°C to +55°C			
Accessories	Included with T4	Integrated alligator clip and tethering loop Bump/calibration plate			
	Available separately	Single unit cradle charger; 10 unit cradle charger; Vehicle charger Clip on dust filter plate I-Test automated bump test and calibration station			

<sup>\*</sup>Toxic and oxygen sensors are not rated for continuous operation above 50°C (122°F)

Product variants and options:	2 gas - Flammable	2 gas - CO	3 gas - H <sub>2</sub> S	3 gas - CO	3 gas - CO (H <sub>2</sub> immune)	4 gas	4 gas (H <sub>2</sub> immune)
Oxygen (O <sub>2</sub> )	•	•	•	•	•	•	•
Flammable	•		•	•	•	•	•
Hydrogen sulphide (H <sub>2</sub> S)			•			•	•
Carbon monoxide (CO)		•		•		•	
Carbon monoxide (CO) - H <sub>2</sub> immune					•		•

#### **Gases and Ranges:**

Gas	Range	Resolution
Oxygen (O₂)	0-30% vol.	0.1% vol.
Flammable	0-100% LEL	1% LEL
Hydrogen sulphide (H <sub>2</sub> S)	0-100ppm	1ppm
Carbon monoxide (CO)	0-1000ppm	1ppm

Crowcon reserves the right to change the design or specification of the product without notice. Check www.crowcon.com for updates.

## www.crowcon.com

UK:

Tel: +44 (0) 1235 557700 Fax: +44 (0) 1235 557718 Email: sales@crowcon.com

US:

Tel: +1 859 957 1039 Toll Free: 800-527-6926 Fax: +859 957 1044 Email: salesusa@crowcon.com

NL

Tel: +31 10 421 1232 Fax: +31 10 421 0542 Email: eu@crowcon.com

#### SG.

Tel: +65 6745 2936 Fax: +65 6745 0467 Email: sales@crowcon.com.sg

ME:

Tel: +971 (0) 4345 1980 Fax: +44 (0) 1235 557718 Email: sales@crowcon.com

IN:

Tel: +91 22 6708 0400 Fax: +91 22 6708 0405 Email: salesindia@crowcon.com

### **T4 Accessories:**



**Cradle charger**Docking station for easy charging



**10 way charger**For charging and storing your T4 fleet



Vehicle charger Effective charging and storage whilst travelling



NEW Portables Pro 2.0 Software
For easy configuration and servicing

**External filter plate**Clip-on filter for dusty environments



**Aspirator plate**Sample atmosphere prior to entry



Easy automated bump testing and calibration solution



**Bump/calibration plate**To apply test gas to T4

Respo Products Respo Safety Solutions Pvt. Ltd. D-595, Kamla Nagar, Agra 282 005 +91-562-2881590; 2885331 1800-180-73776

info@respoproducts.com http://www.respoproducts.com



